





Product Flow Rate Chart in lbs/acre

June 1996

Valmar PT 500

12 groove stainless steel roller, 1/4" gap

*FERTILIZER lbs. per cubic foot	GEAR BOX SETTING										*PT 500 GEARBOX INPUT RATIO
	NO. 1		NO. 2		NO. 3		NO. 4		NO. 5		
	A	B	A	B	A	B	A	B	A	B	
46	54	59	66	73	81	90	99	111	122	<p style="text-align: center;">LOW RATIO</p> 	
48	57	62	70	77	85	95	104	117	128		
50	59	64	72	79	88	98	108	121	132		
52	61	67	75	83	92	102	112	126	138		
54	64	69	78	86	95	106	116	131	143		
56	66	72	81	89	99	110	121	136	148		
58	68	74	84	92	102	114	125	141	153		
60	71	77	87	95	106	118	129	145	159		
62	73	80	89	98	109	121	134	150	164		
64	75	82	92	102	113	125	138	155	169		
66	78	85	95	105	116	129	142	160	175		
68	80	87	98	108	120	133	146	165	180		
70	82	90	101	111	123	137	151	170	185		
72	85	92	104	114	127	141	155	174	190		
74	87	95	107	117	130	145	159	179	196		
76	89	97	110	121	134	149	164	184	201		
46	108.1	118	133	146	162	180	198	223	243		
48	113	124	139	153	170	189	208	234	255		
50	117	128	144	159	176	196	215	242	264		
52	122	133	150	165	183	204	224	252	275		
54	127	139	156	171	191	212	233	262	286		
56	132	144	162	178	198	220	241	272	296		
58	136	149	167	184	205	227	250	281	307		
60	141	154	173	190	212	235	259	291	317		
62	146	159	179	197	219	243	267	301	328		
64	150	164	185	203	226	251	276	310	338		
66	155	169	190	209	233	259	284	320	349		
68	160	174	196	216	240	266	293	330	360		
70	164	179	202	222	247	274	302	339	370		
72	169	185	208	228	254	282	310	349	381		
74	174	190	213	235	261	290	319	359	391		
76	179	195	219	241	268	298	327	368	402		
46	216	236	265	292	324	360	396	446	486		
48	227	247	278	306	340	378	416	468	510		
50	235	256	288	317	352	391	431	484	528		
52	245	267	300	330	367	408	449	505	550		
54	254	277	312	343	381	423	466	524	572		
56	263	287	323	356	395	439	483	543	593		
58	273	298	335	368	409	455	500	563	614		
60	282	308	346	381	423	470	517	582	635		
62	292	318	358	394	437	486	534	601	656		
64	301	328	369	406	451	501	552	621	677		
66	310	338	381	419	465	517	569	640	698		
68	320	349	392	431	479	533	586	659	719		
70	329	359	404	444	493	548	603	679	740		
72	338	369	415	457	508	564	620	698	761		
74	348	379	427	469	522	580	637	717	782		
76	357	390	438	482	536	595	655	737	803		



***IMPORTANT!** To match this chart: Be sure the **GROUND DRIVE RATIO** is set with the **24 TOOTH GEAR DRIVING THE 17 TOOTH GEAR** as shown. (500 PT ONLY)

